Nano LED Tape

10W-240-4K-NANO-LED



IP20 IP44

DESCRIPTION

DRK's LED tape offers a slim, flexible lighting solution for discreet integration into architectural features, joinery and display areas. Suitable for accent, task and concealed lighting, it can be cut at designated points to suit different installation lengths, creating clean lines of light across a variety of interior schemes.

SPECIFICATIONS

Dimensions	1 Metre (L) x 4mm (W) IP20; 1 Metre (L) x 4.5mm (W) IP44
Input Voltage	DC24V
Lumen Output	1100lm/m
LED Efficacy	110lm/W
Color Rendering Index	>97+
Dimming	Driver Dependent
IP Rating	IP20 | IP44
DALI Available	No
Dimension 1	1 Metre (L) x 4mm (W) IP20; 1 Metre (L) x 4.5mm (W) IP44
LED Lifetime	50,000h

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

Nano LED Compatible Profiles (As discussed, this is to actually have links to each profile). +IP at the end of the code for IP rated Tape

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™

Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024