Thyone

THY-BH-B-REC-EM-IP



DESCRIPTION

The THYONE emergency bulkhead is controlled by smart IC, with self-test function. It has two different outputs which are adjustable. Left, right, up, down directional arrow pictogram legends are optional.

IP65
Waterproof

SPECIFICATIONS

Dimensions	340mm (L) x 62mm (D) x 105mm (H)
Input Voltage	AC 220-240V
Lumen Output	200lm
Color Rendering Index	>80
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Integral
Emergency Gear Location	Integral
Housing Material	Polycarbonate

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

IP Rating	IP65
DALI Available	Yes
Dimension 1	340mm (L) x 62mm (D) x 105mm (H).
Mounting Type	Surface Mounted | Recessed
LED Voltage Limit	6.4V
Battery Discharge Current	LiFePO4 6.4V1500mAh
Power Rating (Charging)	3.5W Max
Power Rating (Standing)	<0.5W
Charge Current	220mA±15%
Battery Cut Off	Charge: 7.3V; Discharge: 5.6V
Ambient Temperature (Ta)	0℃~45℃
Case Temperature (Tc)	-40℃-120℃
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024