Telesto

TEL-420-EXIT-B-SM-EM



DESCRIPTION

Self-contained LED Exit Sign with 70M viewing distance. High-efficiency LEDs are evenly laid out at the upper and bottom of the fitting to ensure even light distribution for such a large exit sign without a dark area. The ON/OFF button is on the same side as the manual test button, and the LED indicator is set for easy battery connection and disconnection. Convenient installation is suitable for back mount, ceiling mount, or pendant. Anodised sheet steel housing with black or white colour.

IP20

SPECIFICATIONS

Dimensions	420mm (L) x 75mm (W) x 217mm (H)
Input Voltage	AC 220-240V
Color Rendering Index	>80
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Integral
Emergency Gear Location	Integral
Housing Material	Aluminium and Polycarbonate

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

IP Rating	IP20
DALI Available	Yes
Dimension 1	420mm (L) x 75mm (W) x 217mm (H)
Mounting Type	Surface Mounted | Suspended
LED Voltage Limit	24V
Battery Discharge Current	LiFePO4 6.4V1500mAh
Power Rating (Charging)	2.0W
Power Rating (Standing)	<0.5W
Charge Current	150mA±15%
Battery Cut Off	Charge: 7.3V; Discharge: 5.8V
Ambient Temperature (Ta)	0℃~45℃
Case Temperature (Tc)	-40℃-120℃
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024