Surtur

SUR-NM-EM-W-EMD



DESCRIPTION


LED surface-mounted emergency light with high quality and classic design. High power & efficiency LED. Round lens and oval lens options. LiFePO4 battery, with a long lifetime. D63 Rating.

IP20

SPECIFICATIONS

Dimensions	215mm (L) x 215mm (W) x 54mm (D)
Input Voltage	AC 220-240V
Lumen Output	300lm
LED Efficacy	85lm/W
Color Rendering Index	>70
Emergency Gear Location	Integral
DALI Available	Yes

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

Dimension 1	215mm (L) x 215mm (W) x 54mm (D)
Mounting Type	Surface Mounted
LED Voltage Limit	3.2V
Battery Discharge Current	LiFePO4 6.4V 1500mAh
Power Rating (Charging)	3W Max
Power Rating (Standing)	<0.5W
Charge Current	175mA±15%
Battery Cut Off	Charge: 7.3V; Discharge: 5.6V
Ambient Temperature (Ta)	0℃~45℃
Case Temperature (Tc)	-40℃-120℃
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024