Ariel

ARI-NM-EM-B-EM-IP



DESCRIPTION

This durable, surface-mounted emergency downlight is controlled by a smart IC and features a self-test function. Convenient buckle design ensures effortless installation. IP65-rated enclosures are available.

IP65 Waterproof

SPECIFICATIONS

Dimensions	▯ 175mm (Dia) x 78mm (H)
Input Voltage	AC 220-240V
Lumen Output	240lm
LED Efficacy	68lm/W
Color Rendering Index	>70
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Integral
Emergency Gear Location	Integral

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™

Citation ISO Certification
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024

Housing Material	Polycarbonate
IP Rating	IP65
DALI Available	Yes
Dimension 1	□ 175mm (Dia) x 78mm (H)
Mounting Type	Surface Mounted
Battery Discharge Current	LiFePO46.4V 1500mAh/
Power Rating (Standing)	<0.5W
Charge Current	175mA±15%
Ambient Temperature (Ta)	0℃~45℃
Case Temperature (Tc)	-40℃-120℃
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024