Umbriel

UMB-148-48-NM-EM-H-W-5K-EM



DESCRIPTION


The Umbriel LED emergency downlight is controlled by smart IC with a self-test function. Interchangeable round lens for open area and oval lens for pathways. High-power and efficiency LED. LiFePO4 battery guarantees a long lifetime.

IP20

SPECIFICATIONS

Dimensions	148mm (L) x 148mm (L) x 48mm (D)
Input Voltage	AC 220-240V
Lumen Output	220lm | 450lm
LED Efficacy	73lm/W
Color Rendering Index	>70
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Integral
Emergency Gear Location	Integral
Housing Material	Polycarbonate

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

IP Rating	IP20
DALI Available	Yes
Dimension 1	148mm (L) x 148mm (L) x 33mm (D) | 148mm (L) x 148mm (L) x 48mm (D)
Mounting Type	Surface Mounted
Battery Discharge Current	LiFePO4 6.4V 1500mAh
Power Rating (Standing)	<0.5W
Charge Current	175mA±15%
Ambient Temperature (Ta)	0℃-45℃
Case Temperature (Tc)	-40℃-120℃
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024