Cordelia

COR-140-NM-EM-L-W-5K-EMD



DESCRIPTION

The Cordelia LED emergency surface-mounted downlight is controlled by smart IC with a self-test function. Interchangeable round lens for open area or oval lens for pathways. High-power and efficiency LED. Smart IC control and high-efficiency LED. Lithium battery guarantees a long lifetime.

IP20

SPECIFICATIONS

Dimensions	Ø140mm (Dia) x 48mm (H)
Input Voltage	AC 220-240V
Lumen Output	240lm | 450lm
LED Efficacy	73lm/W
Color Rendering Index	>70
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Integral
Emergency Gear Location	Integral
Housing Material	Polycarbonate
IP Rating	IP20
DALI Available	Yes
Dimension 1	Ø140mm (Dia) x 48mm (H)
Mounting Type	Surface Mounted
Battery Discharge Current	LiFePO46.4V 1500mAh/
Power Rating (Standing)	<0.5W
Charge Current	175mA±15%
Ambient Temperature (Ta)	0°C-45°C
Case Temperature (Tc)	-40°C-120°C
LED Lifetime	50,000h
Warranty	5 years

DIMENSIONS



LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™

Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024