Cupid

CUP-NM-EM-B-H-EM-IP



DESCRIPTION

Round lens for open area application. LiFePO4 battery. High-power and efficiency LED. 80mm adapter ring for larger cutout included.

IP65
Waterproof

SPECIFICATIONS

Dimensions	⌀ 60mm (Dia) x 38.3mm (H)
Input Voltage	AC 220-240V
Lumen Output	250lm | 550lm | 750lm
LED Efficacy	125lm/W
Color Rendering Index	>70
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Remote
Housing Material	Polycarbonate
IP Rating	IP65

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

IK Rating	IK10
DALI Available	Yes
Dimension 1	⌀ 60mm (Dia) x 38.3mm (H)
Cut Out	⌀ 68-75mm
Mounting Type	Recessed
LED Voltage Limit	9.6V
Battery Discharge Current	LiFePO4 6.4V 1500mAh
Power Rating (Charging)	5W Max
Power Rating (Standing)	<0.5W
Charge Current	320mA±15%
Battery Cut Off	Charge: 7.3V; Discharge: 5.6V
Ambient Temperature (Ta)	0℃-45℃
Case Temperature (Tc)	-40℃-120℃
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification Integrated Management System ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024