# Neso

NES-CIRC-TF-W-EM-IP



## DESCRIPTION

Neso IP65 LED Emergency Twin Spot is controlled by smart IC with a self-test function. The robust, white moulded enclosure is rated IK06. Twin spot heads are rotatable for flexible applications. Simple and low-profile design makes the Neso fit its surroundings nicely. Twin side conduit entry. Non-maintained only.

IP65
Waterproof

## DIMENSIONS




## POLAR CURVE

## LUMINAIRE FINISHES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024

## SPECIFICATIONS

| | |
|---|---|
| Dimensions | 267mm (L) x 61.8mm (D) x 259mm (H) |
| Input Voltage | AC 220-240V |
| Lumen Output | 750lm \| 1000lm \| 2000lm |
| LED Efficacy | 110lm/W |
| Color Rendering Index | >80 |
| Dimming | Non-Dimmable \| Switched \| Triac \| 0 to 10V \| DALI 2 \| Bluetooth |
| Control Gear Location | Integral |
| Housing Material | Polycarbonate |
| IP Rating | IP65 |
| IK Rating | IK06 |
| DALI Available | Yes |
| Dimension 1 | 267mm (L) x 61.8mm (D) x 249mm (H) |
| Mounting Type | Surface Mounted |
| LED Voltage Limit | 30V |
| Battery Discharge Current | LiFePO46.4V 3200mAh |
| Power Rating (Standing) | <0.5W |
| Battery Cut Off | Charge: 7.3V; Discharge: 5.6V |
| Ambient Temperature (Ta) | 0℃-45℃ |
| Case Temperature (Tc) | -40℃-120℃ |
| LED Lifetime | 50,000h |
| Warranty | 5 years |

Body W / B / S / R - Custom RAL

## NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification Integrated Management System ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024