Pollux

TNA/2/SP85/R



IP20


DESCRIPTION

The Pollux is a high-quality DALI Self-Test 3-hour switchable emergency lighting module designed to suit a wide range of LED types, circuits and applications. Whilst the Pollux is designed for high-voltage LEDs or longer linear applications, it can run certain self-driven lamps, such as GU10s (subject to testing). The unit is designed to work with lithium iron phosphate (LiFePO4) batteries and is supplied in an IP20 enclosure with an easy-access panel for future battery replacement. The module automatically adjusts the output current to provide the best match between the battery and the load, maximising illumination whilst ensuring full battery life. The pack features a bi-colour charge healthy/fault indicator LED on a flying lead. This range uses the latest LiFePO4 battery technology, dramatically reducing energy consumption and facilities management labour. If a DALI bus is not connected to the Pollux, then the unit will operate as a standalone self-test unit, reporting any faults via a red indication of the charge LED. The Pollux range has been independently certified by TÜV, ensuring the product has been tested for safety and complies with national and international regulations.

SPECIFICATIONS

Dimensions	Module: L320mm x W75mm x H31mm
Input Voltage	55-300V
IP Rating	IP20
DALI Available	Yes
Dimension 1	Module: L320mm x W75mm x H31mm
Mounting Type	Surface Mounted
Current	88mA-14mA
LED Voltage Limit	350V

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

Battery Discharge Current	900mA
Mains Supply	230-240V AC 50/60Hz
Power Rating (Charging)	3.8W 21mA λ = 0.77
Power Rating (Standing)	1.3W 13mA λ = 0.45
Charge Current	225mA nominal
Recharge Period	24 hours
Battery Pack	6.4V 3.8Ah LiFePO4
Battery Cut Off	5V
Ambient Temperature (Ta)	5-35°C
Case Temperature (Tc)	5-55°C
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024