Dian

DIA-110-B-BR-H-3K-2-DA



DESCRIPTION

The DIAN is a high-performance recessed LED downlight featuring a traditional deep reflector design for superior glare control, achieving UGR<19 (24° and 36° beam angles). Delivering high luminous efficiency and excellent colour consistency, it offers multiple beam angles (24°, 36°, 60°) and a 20° adjustable tilt for enhanced design flexibility. With interchangeable reflector finishes and trim options, the DIAN provides versatile lighting solutions without compromising visual comfort or performance.

SPECIFICATIONS

Dimensions	⌀ 110mm x H54mm
Input Voltage	AC 220-240V
Lumen Output	1100lm
LED Efficacy	110lm/W
Color Rendering Index	>80 (>90 Tri-Colour Only)
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Remote

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

Certificate No:447672024

Emergency Gear Location	Remote
Housing Material	Aluminium
IP Rating	IP40
IK Rating	IK06
DALI Available	Yes
Dimension 1	110mm x H54mm
Cut Out	Ø90-95mm
Mounting Type	Recessed
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification Integrated Management System ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024