# Milo

MIL-80-ADJ-B-H-3K-2-DA-REC



## DESCRIPTION

The MILO is an 80mm diameter LED downlight featuring a set-back reflector for reduced glare and visual comfort, achieving UGR<19. Delivering an efficacy of 95lm/W and CRI95+ for excellent colour rendering, it offers a choice of beam angles (15°, 24°, 38°, 60°) for focused accent lighting or wider illumination. Available in recessed and plaster-in mounting options, the range includes an IP65 fixed version and an IP20 adjustable version. DALI 2, Triac and other dimming protocols provide adaptable lighting control.

## DIMENSIONS




## POLAR CURVE



## LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

Certificate No:447672024

## SPECIFICATIONS

| | |
|---|---|
| Dimensions | ⌀ 80mm x H81mm |
| Input Voltage | AC 220-240V |
| Lumen Output | 853lm \| 1024lm |
| LED Efficacy | 85.3lm/W |
| UGR | UGR<19 |
| Color Rendering Index | >95+ |
| Dimming | Non-Dimmable \| Switched \| Triac \| 0 to 10V \| DALI 2 \| Bluetooth |
| Control Gear Location | Remote |
| Housing Material | Aluminium |
| IP Rating | IP20 |
| Dimension 1 | ⌀ 80mm x H81mm |
| Cut Out | ⌀ 68-70mm |
| Mounting Type | Recessed |
| LED Lifetime | 50,000h |
| Warranty | 5 years |

## NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification Integrated Management System ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024