Tiber

TIB-80-ADJ-B-H-3K-2-DA-PI




DESCRIPTION


The TIBER is a versatile LED downlight family featuring a set-back reflector for reduced glare, achieving UGR<19 for enhanced visual comfort. Delivering an efficacy of 95lm/W, it offers a choice of beam angles (15°, 24°, 38°, 60°) for focused accent lighting or wider illumination. Available in fixed and adjustable versions with recessed or plaster-in mounting options, the range also offers an optional honeycomb louvre for additional glare control. Fixed versions are available with an IP65 rating.

UK CA CE RoHS IP20 DALI

DIMENSIONS



POLAR CURVE



DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™

Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024

SPECIFICATIONS

Dimensions	□ 80mm x H67mm
Input Voltage	AC 220-240V
Lumen Output	850lm | 1020lm
LED Efficacy	85lm/W
UGR	UGR<21
Color Rendering Index	>95+
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Remote
Housing Material	Aluminium
IP Rating	IP20
Dimension 1	□ 80mm x H67mm
Cut Out	68-70mm
Mounting Type	Recessed | Plaster-In
LED Lifetime	50,000h
Warranty	5 years

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

Available with a Honeycomb Louvre +HC to end of code

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™

Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024