Gila

GIL-80-ADJ-B-H-3K-1-TR-REC




DESCRIPTION

The GILA is an adjustable LED downlight family, available with recessed or plaster-in mounting options for a clean, integrated finish. A choice of beam angles (15°, 24°, 38°, 60°) allows for focused accent lighting or wider illumination, with adjustable positioning to direct light where required. An optional honeycomb louvre provides additional glare control, while DALI 2, Triac and other dimming options support adaptable lighting control. The range is rated IP20.

SPECIFICATIONS

Dimensions	Ø80mm x H67mm
Input Voltage	AC 220-240V
Lumen Output	850lm | 1020lm
LED Efficacy	85lm/W
UGR	UGR<21
Color Rendering Index	>95+
Dimming	Non-Dimmable | Switched | Triac | 0 to 10V | DALI 2 | Bluetooth
Control Gear Location	Remote
Housing Material	Aluminium
IP Rating	IP20
Dimension 1	Ø80mm x H67mm
Cut Out	68-70mm
Mounting Type	Recessed | Plaster-In
LED Lifetime	50,000h
Warranty	5 years

DIMENSIONS



LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

Available with a Honeycomb Louvre +HC to end of code

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

Certificate No:447672024