# Gila

GIL-80-ADJ-B-H-3K-1-TR-PI



## DESCRIPTION

The GILA is an adjustable LED downlight family, available with recessed or plaster-in mounting options for a clean, integrated finish. A choice of beam angles (15°, 24°, 38°, 60°) allows for focused accent lighting or wider illumination, with adjustable positioning to direct light where required. An optional honeycomb louvre provides additional glare control, while DALI 2, Triac and other dimming options support adaptable lighting control. The range is rated IP20.

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

Certificate No:447672024

## SPECIFICATIONS

| | |
|---|---|
| Dimensions | ⌀ 80mm x H67mm |
| Input Voltage | AC 220-240V |
| Lumen Output | 850lm \| 1020lm |
| LED Efficacy | 85lm/W |
| UGR | UGR<21 |
| Color Rendering Index | >95+ |
| Dimming | Non-Dimmable \| Switched \| Triac \| 0 to 10V \| DALI 2 \| Bluetooth |
| Control Gear Location | Remote |
| Housing Material | Aluminium |
| IP Rating | IP20 |
| Dimension 1 | ⌀ 80mm x H67mm |
| Cut Out | 68-70mm |
| Mounting Type | Recessed \| Plaster-In |
| LED Lifetime | 50,000h |
| Warranty | 5 years |

## DIMENSIONS




## POLAR CURVE

## LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

## NOTES

Available with a Honeycomb Louvre +HC to end of code

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024