RGB and RGBW LED Tape

9W-420-RGB-LED



DESCRIPTION


DRK's LED tape offers a slim, flexible lighting solution for discreet integration into architectural features, joinery and display areas. Suitable for accent, task and concealed lighting, it can be cut at designated points to suit different installation lengths, creating clean lines of light across a variety of interior schemes.

IP65
Waterproof

SPECIFICATIONS

Dimensions	1 Metre (L) x 10mm (W) IP20 ; 1 Metre (L) x 12mm (W) IP65
Input Voltage	DC24V
Lumen Output	375lm/m
LED Efficacy	41.66lm/W
Dimming	Driver Dependent
IP Rating	IP20 | IP65
DALI Available	No
Dimension 1	1 Metre (L) x 10mm (W) IP20 ; 1 Metre (L) x 12mm (W) IP65
LED Lifetime	50,000h

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

Compatible Profiles - (As discussed, this is to actually have links to each profile). +IP at the end of the code for IP rated Tape

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™

Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024