# Eris

ERI-TM-W-EMD



## DESCRIPTION

The ERIS is a 240V track-mounted non-maintained emergency fitting with a compact design and integral emergency control gear. Delivering 380lm with a 5000K colour temperature, the Eris incorporates a LiFePO4 battery for a long service life.

IP20

## SPECIFICATIONS

| | |
|---|---|
| Dimensions | L193mm x H89mm x W53mm |
| Input Voltage | AC 220-240V |
| Lumen Output | 380lm |
| LED Efficacy | 152lm/W |
| Color Rendering Index | >70 |
| Control Gear Location | Integral |

## DIMENSIONS




## POLAR CURVE

## LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

## NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™

Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024

| | |
|---|---|
| Emergency Gear Location | Integral |
| Housing Material | Polycarbonate |
| IP Rating | IP20 |
| IK Rating | IK06 |
| Dimension 1 | L193mm x H89mm x W53mm |
| Mounting Type | Track Mounted |
| Battery Pack | LiFePO4 26650 6.4V 3200mA h |
| LED Lifetime | 50,000h |
| Warranty | 5 years |

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024