Eris

ERI-TM-B-EM



DESCRIPTION

The ERIS is a 240V track-mounted non-maintained emergency fitting with a compact design and integral emergency control gear. Delivering 380lm with a 5000K colour temperature, the Eris incorporates a LiFePO4 battery for a long service life.

IP20

SPECIFICATIONS

Dimensions	L193mm x H89mm x W53mm
Input Voltage	AC 220-240V
Lumen Output	380lm
LED Efficacy	152lm/W
Color Rendering Index	>70
Control Gear Location	Integral

DIMENSIONS



POLAR CURVE

LUMINAIRE FINISHES

Body W / B / S / R - Custom RAL

NOTES

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification ISO 9001: 2015 ISO 14001: 2015 REGISTERED
Certificate No:447672024

Emergency Gear Location	Integral
Housing Material	Polycarbonate
IP Rating	IP20
IK Rating	IK06
Dimension 1	L193mm x H89mm x W53mm
Mounting Type	Track Mounted
Battery Pack	LiFePO4 26650 6.4V 3200mA h
LED Lifetime	50,000h
Warranty	5 years

DRK Lighting LTD
Unit 2, Silverglade Business Park,
Leatherhead Road, Chessington,
KT9 2QL

info@drklighting.co.uk
+44 (0)207 018 2202
www.drklighting.co.uk

bsi Certified Remanufacturer KITEMARK™
Citation ISO Certification
Integrated Management System
ISO 9001: 2015
ISO 14001: 2015
REGISTERED
Certificate No:447672024